

**AMERICANA®**

**FP410\*\*-220  
/ FP420\*\*-220  
Series  
Ceiling Fans**



Short Fan Assembly - FP410**-220	
Overall Height (w/o Light Kit)	25"
Blade Sweep	*
Base Diameter	16¾"
Mounting Diameter (3-hole; centerline)	13"
Weight: (w/o Light Kit)	32 lbs

Long Fan Assembly - FP420**-220	
Overall Height (w/o Light Kit)	39"
Blade Sweep	*
Base Diameter	16¾"
Mounting Diameter (3-hole; centerline)	13"
Weight: (w/o Light Kit)	41 lbs

\*Blade sweep varies depending on blade selection, see chart on page 79

Available Finishes	
AB	Antique brass
BL	Black

Ordering Information	
Catalog No.	Description
FP410**-220	Short fan assembly
FP420**-220	Long fan assembly
FP1018	Reversible oak/walnut blade set (sold separately)

**INSTALLATION REQUIREMENTS:**

Requires 3/4" plywood wall backing, able to support at least 100 lbs. Fan base is secured to 3/4" plywood backing using three 5/16" lag bolts. Ceiling backing to be supplied by owner or contractor.

**ELECTRICAL REQUIREMENTS:**

Surface mounted electrical junction box centered in mounting location with a grounded electrical supply line of 220~240 volts AC, 50 Hz, 5 amp circuit.

**MOTOR SPECS:**

FK2100-220 motor is designed for optimal performance with this fan. Reversing switch and 3-speed pull-chain included.

**BLADES:**

A variety of 4- and 5-blade sets are available. 5-blade sets are available in palm, bamboo, wood and composite materials. 4-blade sets are made of wood and require the use of BH20 series blade holders (not included). 4-blade sets will increase speed and airflow. See our catalog or visit [www.fanimation.com](http://www.fanimation.com) for blade options.

*Note: Fan speeds will vary according to blade set—material, shape and size of blade. In general, smaller blades will turn faster than bigger ones and narrower blades will turn faster than wider ones.*

**CONTROL OPTIONS:**

Optional C1-220, C2-220, C3-220 and C6-220 wall controls and CR4WH-220 remote control (with receiver units ) are available—sold separately. Instructions are provided with each control.

**LIGHTING OPTIONS:**

Optional lighting fitters and light kits are available—see our catalog or visit [www.fanimation.com](http://www.fanimation.com).

**LOCATION USAGE:**

FP410AB-220/FP420AB-220 are rated for dry locations only. FP410BL-220/FP420BL-220 are rated for dry and damp locations.