
TORTO™



FP7902BN Ceiling Fan



	Α	В
Fan w/6" downrod	16.50″	15.00″
Fan w/12" downrod	22.50"	21.00"
Fan w/18" downrod	28.50"	27.00"
Fan w/24" downrod	34.50"	33.00"
Fan w/36" downrod	46.50"	45.00"
Fan w/48" downrod	58.50"	57.00"
Fan w/60" downrod	70.50″	69.00"
Fan w/72" downrod	82.50″	81.00″

Available Finish Brushed Nickel with Brushed Nickel Blades and Opal Frosted Glass

Airflow / Energy Efficiency Info (120V)							
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts		
High	96	4425	80	0.47	56		
Med	67	2849	108	0.39	26		
Low	47	2057	141	0.31	15		

Energy Guide FTC					
Power (W _{ave})	Total Air Delivery (CFM _{ave})	Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)		
39	1124	11	29		

Light Bulb Information (120V)					
Bulb Type	Watts	Lumens Amount	Color Temp	CRI	
LED	18	1350	3000	80%	

INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

172 x 20 AC motor is designed for optimal performance with this fan.

BLADE SET:

A set of three composite blades is included.

CONTROL OPTIONS:

BTT9R bluetooth hand-held remote control with wall mount is included. Push button remote control has 3 fan speeds, infinite light levels, reverse and off button. Optional C21 wall control and TR20WH hand held remote are available—sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

One 18-watt LED included.

DOWNROD OPTIONS:

Fan comes with a 1" dia. x 6" long downrod (DR1-6). Optional downrods available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 27°. Most sloped ceiling installations require a downrod longer than the standard 6" downrod. Optional sloped ceiling ball kits (SCB1-52) are available for slope angles greater than 27° and up to 42°. Call technical support for more information.

LOCATION USE:

Fan is rated for dry and damp locations.