Draco[®] FP3220CH




SPECIFICATION SHEET



celebrating 25 years

Product Specifications subject to change

Draco® Fan Assembly – FP3220CH



Available Finishes				
СН	Chrome			

Distance from Ceiling to Bottom of Fan	Α	
Fan w/6" downrod	18″	
Fan w/12" downrod	24″	
Fan w/18" downrod	30″	
Fan w/24" downrod	36″	
Fan w/36" downrod	48″	
Fan w/48" downrod	60″	
Fan w/60" downrod	72″	
Fan w/72" downrod	84″	

Airflow / Energy Efficiency Info (120V)							
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts		
High	150	6837	93	0.61	74		
Med	111	4808	112	0.53	43		
Low	65	2490	146	0.36	17		

INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 50 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

188 x 25 motor is designed for optimal performance with this fan.

BLADES:

A set of three composite blades are included with this fan.

CONTROL OPTIONS:

C24 hand-held remote control with canopy-style receiver unit (RECAN68) is included. Push button remote control has 3 fan speeds, infinite light levels and off button. Reversing switch located inside fan housing on upper socket housing. Optional C25 wall control is available—sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

3-bulb downlight fixture with three 40-watt candelabra bulbs is included. Maximum downlight wattage not to exceed 120 watts.

DOWNROD OPTIONS:

Fan comes with a $\frac{1}{2}$ " dia. x 6″ long downrod (DR6). Optional downrods are available in 12″, 18″, 24″, 36″, 48″, 60″ and 72″ lengths. A downrod coupler is available for installations requiring a downrod longer than 72″. Fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6″ downrod. Optional sloped ceiling ball kits (SCB52) are available for slope angles greater than 30° and up to 52°. Call technical support for more information.

LOCATION USE:

Fan is rated for dry locations only.



10983 Bennett Parkway
Zionsville, IN 46077
Toll Free (888) 567-2055
FAX (866) 482-5215
Outside U.S. call (317) 733-4113
Visit Our Website www.fanimation.com

