







INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

DC-165NM sensorless DC motor is designed for optimal performance with this fan. Fan is Energy Star Rated.

BLADES:

A Set of three 31" beech wood for black, natural and walnut finish blade. Button wood for the matte paper white finish blade. —sold separately.

LIGHTING OPTIONS:

Optional light kit with 17-watt LED is available—sold separately.

CONTROL OPTIONS:

TR39RJ hand-held DC fan remote control is included. Push botton remote control has 6 fan speeds, infinite light levels, reverse and off button. Optional TW40 wall conrtol is available—sold separately

DOWNROD OPTIONS:

Fan comes with 1" dia. x 4.5" long downrod (DR1-45). Optional downrods available in 12", 18", 24", 36", 48", 60", and 72"

	A ₁	\mathbf{A}_{2}	В
Fan w/4.5" downrod	13.61"	12.65"	12.07"
Fan w/12" downrod	21.11"	20.15"	19.57"
Fan w/18" downrod	27.11"	26.15"	25.57"
Fan w/24" downrod	33.11"	32.15"	31.57"
Fan w/36" downrod	45.11"	44.15"	43.57"
Fan w/48" downrod	57.11"	56.15"	55.57"
Fan w/60" downrod	69.11"	68.15"	67.57"
Fan w/72" downrod	81.11"	80.15"	79.57"

Available Finishes-Fan / Housing Assemb		
BL	Matte Black with Matte Black Housing	
GZ	Galvanized with Galvanized Housing	
RMW	Matte Paper White with Matte Paper White Housing	

Sold Separate Parts			
Close to Ceiling Kit	Light Kit	Blade	
Galvanized	Galvanized	Black	
Matte Black	Matte Black	Matte Paper White	
Watte Diack	Watte Diack	Natural	
Matte Paper White	Matte Paper White	Walnut	

Airflow / Energy Efficiency Info (120V) Energy Star test with Beech Wood Blade					
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
I	50	2014	1259	0.30	2
II	72	2975	1144	0.50	3
III	92	3724	955	0.60	4
IV	115	4595	707	0.10	7
V	136	5671	567	0.14	10
VI	157	6349	418	0.20	15

Energy Guide FTC test with Beech Wood Blade				
Power (W _{ave})	Total Air Delivery (CFM _{ave})	Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)	
14	4100	4	285	

۱٠	Light Bulb Information (120V)				
	Bulb Type Watts		Lumens Amount	Color Temp	CRI
	LED	17	1590	3000	80%

lengths. A downrod coupler is available for installations requiring a downrod longer than 72". Fan can be mounted on a sloped upto 19°. Most sloped ceiling installations require a downrod longer than the standard 4.5" downrod. Optional close-to-ceiling kit is available as well—sold separately. Optional sloped ceiling kits (SCK1-52) are available for up to 42°. Call technical support for more information.

LOCATION USE:

Fans are good to use on dry and damp locations.