

## WINDPOINTE® SERIES

# MA7500\*\*-220 Fan Motor Assembly



TUV/GS Efficiency Info (220V)			
Fan Speed	Max RPM	Amps	Watts
High	113	0.24	62
Med	80	0.17	33
Low	53	0.12	18

Available Finish
MA7500AB-220 – Antique Brass
MA7500OB-220 – Oil-Rubbed Bronze
MA7500RS-220 – Rust

### INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 50 lbs.

### ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 220~240 volts AC, 50 Hz, 5 amp circuit.

### MOTOR SPECS:

188 x 15-220 AC motor is designed for optimal performance with this fan.

### FAN SPEEDS / BLADES:

3 fan speeds with pull chain and reversing switch (on switch cup housing). Speeds will vary depending on blade size and type. All blade sets are sold separately. See our catalog or visit [www.fanimation.com](http://www.fanimation.com) for available blade options.

### CONTROL OPTIONS:

Optional C1-220, C2-220, C3-220 and C6-220 wall controls and CRL4WH-220 remote control (with receiver unit) are available—sold separately. Instructions are provided with each control.

### LIGHTING OPTIONS:

Optional lighting fitters and light kits are available. See our catalog or visit [www.fanimation.com](http://www.fanimation.com) for lighting options.

### DOWNROD OPTIONS:

Fan comes with a 1" dia. x 6" long downrod (DR1-6). Optional downrods are available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6" downrod. Optional sloped ceiling ball kits (SCB1-52) are available for up to 52°. Optional close-to-ceiling kit is available as well-sold separately. Call technical support for more information.

### LOCATION USE:

MA7500AB-220 is rated for dry locations only. MA7500OB-220 and MA7500RS-220 are rated for dry and damp locations. Damp location rated with use of woven bamboo or all-weather composite blades.