



	A	В
Fan In Close to Ceiling Configuration	9.63″	7.72″
	Α	В
	<i>,</i> ,	
Fan w/4.5" downrod	13.20"	11.10"
Fan w/4.5" downrod Fan w/12" downrod		
	13.20″	11.10"

	Α	В
Fan w/4.5" downrod	13.20″	11.10″
Fan w/12" downrod	20.70″	18.60″
Fan w/18" downrod	26.70"	24.60″
Fan w/24" downrod	32.70″	30.60″
Fan w/36" downrod	44.70″	42.60"
Fan w/48" downrod	56.70″	54.60″
Fan w/60" downrod	68.70″	66.60″
Fan w/72" downrod	80.70″	78.60″

Net Hanging Weight: 16.12 lbs

INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

153 x 15 AC motor is designed for optimal performance with this fan.

BLADES:

A set of five 21" traditional all-weather composite blades is included.

CONTROL OPTIONS:

Optional CW5, WC1WH, WC2WH, WR500WH and WR501WH wall controls available—sold separately. Optional BTCR9, CRL4WH and CR500 remote controls, BTR9 receiver unit and WFR50 WiFi receiver unit are available—sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Optional lighting fitters and light kits are available.

See our catalog or visit www.fanimation.com for available lighting options.

DOWNROD OPTIONS:

Dual mount for flush mount application or 1" dia x 4.5" long downrod. Optional downrods available in 12", 18", 24", 36",48", 60", and 72" lengths. A downrod coupler is available for installations requiring a downrod longer than 72". Fan can be mounted on a sloped ceiling up to 14°. Most sloped ceiling installations require a standard 18" downrod or longer downrod. Optional sloped ceiling kits (SCK1-52) are available for slope an angles up to 42°. Optional close-to-ceiling kit is available as well—sold separately. Call technical support for more information.

Available Finishes			
Fan / Housing Assembly	Blades - Traditional		
BL – Black	Black composite blade		
MW – Matte white	Matte white composite blade		
OB – Oil-rubbed bronze	Walnut composite blade		
SN – Satin nickel	Cherry composite blade		

Airflow / Energy Efficiency Info (120V)-Hugger				ıgger	
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High	146	4056	83	0.41	49
Med	106	2491	119	0.27	21
Low	53	1430	178	0.16	8

Airflow / Energy Efficiency Info (120V)-Standard				ndard	
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High	146	4404	91	0.40	48
Med	110	2776	133	0.27	21
Low	54	1534	190	0.17	8

	ger)		
Power (W _{ave}) Total Air Delivery (CFM _{ave})		Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)
30	2825	8	95

Energy Guide FTC (Standard)				
Power (W _{ave})	Total Air Delivery (CFM _{ave})	Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)	
29	3059	8	104	

LOCATION USE:

Fan is rated for dry and damp locations. This fan is for room up to 400 sq ft.