




AIREFLEX™

LP7675** 52" Ceiling Fan





Net Hanging Weight: 11.25 lbs	Floor _
	•

	Α	В
Fan w/4.5" downrod	13.14"	10.53"
Fan w/12" downrod	20.64"	18.03"
Fan w/18" downrod	26.64"	24.03"
Fan w/24" downrod	32.64"	30.03"
Fan w/36" downrod	44.64"	42.03"
Fan w/48" downrod	56.64"	54.03"
Fan w/60" downrod	68.64"	66.03"
Fan w/72" downrod	80.64"	78.03"

INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

100 x 30 DC motor is designed for optimal performance with this fan. Fan is Energy Star Rated.

BLADES:

A set of three 24" aluminum blades is included.

CONTROL OPTIONS:

TR305S hand-held remote control is included. Push button remote control with 16 fan speeds, fresh air, reverse, ON/OFF dimmer light levels, color temperature, fan/light timer, home away, safe exit and off button. Optional TW306 wall control is available — sold separately. Instructions is provided with each control.

LIGHTING OPTIONS:

One 18-watt CCT LED (3000K/4000K/5000K) included.

Power (Wave)	Total Air Delivery (CFMave)	Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)
15	4500	4	296

Energy Guide FTC

Available Finishes

Blade and Opal Frosted Glass

Airflow / Energy Efficiency Info (120V)

CFM

5910

3513

809

LBL

LBS

Fan Speed

High (16th)

Med (9th)

Low (1th)

Glass

Max RPM

161

100

29

Black with Black Blade and Opal Frosted

Brushed Satin Brass with Matte White

CFM / Watts

268

620

415

Amps

0.35

0.10

0.05

Watts

22

6

2

Light Bulb Information (120V)					
Bulb Type	Watts	QTY	Lumens Amount	Color Temp	CRI
LED	18	1	1600	3000/4000/5000	90%

DOWNROD OPTIONS:

Fan comes with a 1" dia. x 4.5" long downrod (DRT1-4.5). Optional downrods are available in 12",18", 24", 36", 48", 60" and 72". For installations requiring a longer downrod, a downrod coupler is available. Fan can be mounted on a sloped ceiling up to 19°. Most sloped ceiling installations require a standard 18" downrod or longer downrod. Optional sloped ceiling kits (SCK1-52) are available for up to 42°. Call technical support for more information.

LOCATION USE:

Fan is rated for dry and damp locations. This fan is for rooms up to 400 sq ft.