



INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

82 x 20 AC motor is designed for optimal performance with this fan.

CONTROL OPTIONS:

TR500S hand-held remote control is included. Push button remote control with variable fan speeds, infinite light levels and off button. Optional WC2WH and WR501WH wall controls are available — sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Four 4-watt LED bulbs included.

DOWNROD OPTIONS:

Fan comes with a 1" Dia. x 4.5" downrod (DRT1-45). Optional downrods are available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 19°. Most sloped ceiling installations require a standard 4.5" downrod or longer downrod. Optional close-to-ceiling kit is available as well — sold separately. Optional sloped ceiling kits (SCK1-52) are available for up to 42° Call technical support for more information.

LOCATION USE:

Fan is rated for dry and damp locations. This fan is for room up to 100 sq ft.



VINTERE™

LP8350BLAZ (Lowes Item #2483972)

20" Ceiling Fan

| | Α | В |
|--------------------|--------|--------|
| Fan w/4.5" downrod | 12.80″ | 10.44" |
| Fan w/12" downrod | 20.30″ | 17.94″ |
| Fan w/18" downrod | 26.30" | 23.94" |
| Fan w/24" downrod | 32.30" | 29.94" |
| Fan w/36" downrod | 44.30″ | 41.94″ |
| Fan w/48" downrod | 56.30" | 53.94" |
| Fan w/60" downrod | 68.30″ | 65.94" |
| Fan w/72" downrod | 80.30″ | 77.94″ |

| Available Finishes | | | |
|--------------------|-----------------------------------|--|--|
| LAZ | Aged Bronze with Aged Bronze Cage | | |

| Airflow / Energy Efficiency Info (120V) | | | | | |
|---|---------|------|-------------|------|-------|
| Fan Speed | Max RPM | CFM | CFM / Watts | Amps | Watts |
| High | 1400 | 1472 | 37 | 0.33 | 40 |
| Med | 976 | 986 | 44 | 0.27 | 23 |
| Low | 640 | 541 | 47 | 0.19 | 11 |

| Energy Guide FTC | | | | |
|--|------|--------------------------------------|--------------------------------------|--|
| Power (W _{ave}) Total Air Delivery (CFM _{ave}) | | Estimated Yearly Energy Cost (\$) | Ceiling Fan Efficiency (CFM/W) | |
| 27 | 1190 | 8 | 43 | |

| Lighting Information (120V) | | | | | | |
|-----------------------------|-------|-----|------------------|---------------------|------------|-----|
| Bulb Type | Watts | QTY | Lumens Amount | Delivered Lumens | Color Temp | CRI |
| LED | 4 | 4 | 1280 | 1508 | 2700 | 90% |